

POWERGUARD®
World Class technology - 100% Australian owned


EXTREME HOME THEATRE PROTECTOR

NOTHING PROTECTS LIKE POWERGUARD



**MODEL NO:
PGXH3708**

THIS MODEL PROTECTS AGAINST:



1. Low Voltage
2. High Voltage – Surges
3. High Voltage – Spikes
4. RFI and EMI
5. Power Loss, Blackout
6. Lightning#

Lightning protection via connected equipment warranty



PROTECTION FEATURES

MORE THAN DOUBLE THE AC MAINS PROTECTION OF CONVENTIONAL MULTI OUTLET BOARDS

- Cascade multi stage filtering, diverts for spike protection and RFI & EMI filtration
- Patented Active intelligent sensing, isolates for true AC mains Over Voltage, Surge and phase loss protection

- Under voltage, Brown out (Sag) protection
- Antenna Splitter/Coaxial protection works to protect by diverting potentially damaging induced voltages to a direct connected earth

PowerGuard Extreme Home Theatre Protector PGXH3708 is a combination of the PowerGuard Original, Continuous Power Filter and Ultra Filter. The protection strategy is arranged with the PowerGuard Original patented Active Intelligent Sensing front ending the whole of the PGXH protection to the supply voltage input, protecting all eight outlets and is then linked in conjunction with Cascade Multi-stage Filtering on the AC Mains. The Primary bank of six outlets is CPF filtered with additional crossover filtering to the Isolated Dual Outlet bank, arranged in a Cascade configuration. The Isolated Dual Outlet bank is totally isolated from the Primary bank and final filtered.

The AC filter is a similar specification as the Continuous Power Filter for clamping and energy dissipation, but is arranged in a cascade, multi-stage circuit design – the benefit is that rather than totally block all the excess energy and risk causing a back EMF, that could damage neighbouring unprotected equipment, the protection is designed to capture, absorb and dissipate the excess energy or transient interference. Residual interference is captured by each successive stage; the cascade circuit design captures any graduated overflow at each successive stage of the filter providing cleaner power.

PowerGuard Extreme Home Theatre Protector antenna splitter provides greater protection by design. Low pass arresters work to protect by diverting potentially damaging induced voltages to a direct connected earth.

RECOMMENDED APPLICATIONS

- Home Theatre Systems
- LCD & Plasma televisions
- Amplifiers and Stereo components
- Projectors
- Digital boxes
- VCR and DVD recorders

SPECIFICATION – AC ELECTRICAL – SPIKE ARRESTING AND FILTRATION

Electrical Rating	110 ~ 230/240V AC 50/60Hz 10 Amps (2400w)	Clamping Voltage	275V
Protection Modes	Differential Mode (Active – Neutral) Common Mode (Active – Neutral Earth)	Maximum Amps Absorption	55,000 Amps
Reaction Time	1 to 3 n/Seconds	Maximum Joules Absorption	1,500 Joules
		Operation Temperature	-10 to 70 °C

SPECIFICATION – AC ELECTRICAL – OVER/UNDER VOLTAGE

Electrical Rating	230/240V 50Hz or 110/120V 60Hz 10 Amps (2400w)	Detection Time	<1 m/Second (non destructive) <1 n/Second (destructive)
High Voltage Rating	265 Volts (Factory Set)	Reaction Time	<5 m/Seconds (non destructive) <1 n/second (destructive)
Low Voltage Rating	190 Volts (Factory Set)	Operation Temperature	-10 to 70 °C

COAXIAL PROTECTION/ANTENNA SPLITTER – RF CABLE PROVIDED



\$120,000
CONNECTED EQUIPMENT WARRANTY

Powerguard Unit 6/7 Revelation Close Tighes Hill NSW 2297
Orders and Enquiries: Phone: 1800 077 501 Fax: 1800 247 501
International Orders and Enquiries: Phone: +61 2 4940 8714 Fax: +61 2 4962 4371
Website www.powerguard.com.au
Designed and Engineered in Australia. Made in China.